

BC1595 PHOSPHATE/POLYMER INTERNAL TREATMENT

DESCRIPTION

BC1595 is designed for phosphate precipitating internal treatment programs. BC1595 provides a high concentration of phosphate and a low concentration of a carboxylated organic polymer designed for this application. BC1595 is typically used in systems with softened make-up water.

BC1595 is normally used in combination with other treatment chemicals to provide a complete boiler treatment program.

FEATURES AND BENEFITS

- Improves boiler reliability and cleanliness
- Standard phosphate to polymer ratio
- Contains an effective polymer for deposit control
- Polymer is stable over a wide range of temperatures and pressures

PRODUCT FEED AND CONTROL

BC1595 is fed continuously to the system being treated. The product may either be fed neat directly from the shipping container or mixed in a chemical feed tank using good quality condensate, softened water, or feedwater. Tanks, pumps, piping and valves should be made of stainless steel, polyethylene, or PVC.

Control of BC1595 is by a filtered phosphate test. The technical specialist servicing the facility will provide specific treatment control levels based on system conditions.

PHYSICAL PROPERTIES

Physical properties of BC1595 are shown on the Material Safety Data Sheet (MSDS), a copy of which is available upon request.

STORAGE AND HANDLING

Keep in a tightly closed container. Store indoors. Recommended storage temperature is 50° F - 105° F (10° C - 40° C). Do not reuse container. Dispose of empty container in compliance with federal, state/provincial and local laws and regulations.

ENVIRONMENTAL, HEALTH, AND SAFETY

For detailed information, consult the material safety data sheet (MSDS).

PACKAGING

BC1595 is available in a wide variety of customized containers and delivery methods.

