

BC1287

ALL-IN-ONE ALL POLYMER INTERNAL TREATMENT

DESCRIPTION

BC1287 is an All-in-One All-Polymer internal treatment product. BC1287 includes polymer for deposit control and sulfite for removing oxygen from the boiler water. BC1287 is typically used in systems with softened make-up water. BC1287 does not include alkalinity builder or neutralizing amine.

FEATURES AND BENEFITS

- Improves boiler reliability and cleanliness
- Single drum product for ease of use
- Utilizes copolymer for excellent control of hardness and iron deposition
- Polymer is stable over a wide range of temperatures and pressures

PRODUCT FEED AND CONTROL

BC1287 is fed continuously to the system being treated. The product may either be fed neat directly from the shipping container or mixed in a chemical feed tank using good quality condensate, softened water, or feedwater. Tanks, pumps, piping and valves should be made of stainless steel, polyethylene, or PVC.

BC1287 is controlled by measuring boiler water sulfite residual concentration. The technical specialist servicing the facility will provide specific treatment control levels based on system conditions.

PHYSICAL PROPERTIES

Physical properties of BC1287 are shown on the Material Safety Data Sheet (MSDS), a copy of which is available upon request.

STORAGE AND HANDLING

Keep in a tightly closed container. Store indoors. Recommended storage temperature is 50° F - 105° F (10° C - 40° C). Do not reuse container. Dispose of empty container in compliance with federal, state/provincial and local laws and regulations.

ENVIRONMENTAL, HEALTH, AND SAFETY

For detailed information, consult the material safety data sheet (MSDS).

PACKAGING

BC1287 is available in a wide variety of customized containers and delivery methods.