

## **OS1137 SULFITE-BASED OXYGEN SCAVENGER**

### **DESCRIPTION**

OS1137 is a powdered sodium sulfite which, when added to boiler feedwater, removes dissolved oxygen. By acting as an oxygen scavenger, OS1137 is used to control corrosion and pitting caused by the presence of dissolved oxygen.

### **FEATURES AND BENEFITS**

- Improves boiler system reliability and longevity
- Removes corrosive oxygen from the boiler feedwater and boiler water

### **PRODUCT FEED AND CONTROL**

OS1137 must be mixed in a chemical feed tank using good quality condensate, softened water, or feedwater. An agitator is required to assure complete dissolution of the product. OS1137 may be mixed with most common chemicals used for boiler treatment. Tanks, pumps, piping and valves should be made of stainless steel, polyethylene, or PVC.

OS1137 is normally controlled by a sulfite test on the boiler water. Control ranges can vary widely depending upon both makeup water characteristics and system operating conditions and will be specified by the technical representative servicing the facility.

### **PHYSICAL PROPERTIES**

Physical properties of OS1137 are shown on the Material Safety Data Sheet (MSDS), a copy of which is available upon request.

### **STORAGE AND HANDLING**

Keep in a tightly closed container. Store indoors. Do not reuse container. Dispose of empty container in compliance with federal, state/provincial and local laws and regulations.

### **ENVIRONMENTAL, HEALTH, AND SAFETY**

For detailed information, consult the material safety data sheet (MSDS).

### **PACKAGING**

OS1137 is available in a wide variety of customized containers and delivery methods.