

## OS1337 SULFITE-BASED OXYGEN SCAVENGER

### DESCRIPTION

OS1337 highly concentrated acidic sulfite solution which, when added to boiler feedwater, removes dissolved oxygen. By acting as an oxygen scavenger, OS1337 is used to control corrosion and pitting caused by the presence of dissolved oxygen.

### FEATURES AND BENEFITS

- Improves boiler system reliability and longevity
- Removes corrosive oxygen from the boiler feedwater and boiler water

### PRODUCT FEED AND CONTROL

OS1337 must be mixed in a chemical feed tank using good quality condensate, softened water, or feedwater. An agitator is required to assure complete dissolution of the product. OS1337 may be mixed with most common chemicals used for boiler treatment. Tanks, pumps, piping and valves should be made of stainless steel, polyethylene, or PVC. Neat product is low pH and can be corrosive to feedwater systems.

OS1337 is normally controlled by a sulfite test on the boiler water. Control ranges can vary widely depending upon both makeup water characteristics and system operating conditions and will be specified by the technical representative servicing the facility.

### PHYSICAL PROPERTIES

Physical properties of OS1337 are shown on the Material Safety Data Sheet (MSDS), a copy of which is available upon request.

### STORAGE AND HANDLING

Keep in a tightly closed container. Store indoors. Recommended storage temperature is 50° F - 105° F (10° C - 40° C). Do not reuse container. Dispose of empty container in compliance with federal, state/provincial and local laws and regulations.

### ENVIRONMENTAL, HEALTH, AND SAFETY

For detailed information, consult the material safety data sheet (MSDS).

### PACKAGING

OS1337 is available in a wide variety of customized containers and delivery methods.